



Certificate no.:  
**TAA00003FG**

# TYPE APPROVAL CERTIFICATE

## This is to certify:

that the **Personal Computer**

with type designation(s)  
**HP Z4 G5 Workstation**

issued to

**Mariner Systems (UK) Ltd.**  
**Wokingham, Berkshire, United Kingdom**

is found to comply with

**DNV rules for classification – Ships, offshore units, and high speed and light craft**

## Application:

Products approved by this certificate are accepted for installation on all vessels classed by DNV.

Approved only with Mariner Kit shown on page 2.

## Location classes:

Temperature	D
Humidity	B
Vibration	A
EMC	B
Enclosure	A / IP 20

Issued at **Høvik** on **2024-09-06**

for **DNV**

This Certificate is valid until **2029-09-05**.

DNV local unit: **Newcastle-upon-Tyne**

Approval Engineer: **Nikolai Arntzen**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

HP Z4 G5 Workstation.

Verified for nominal supply voltage: 230 V ~ 50/60 Hz and 115 V ~ 60 Hz

## Application/Limitation

Approval **ONLY** applies when used in conjunction with Mariner Systems (UK) Ltd:

### Mariner Kit:

MS3110 HP Z4 G5 Workstation (Desktop configuration)

MS3120 HP Z4 G5 Workstation (Tower configuration)

Only to be installed together with in-line power filter RF 1010-MST-A.

Shielded cable is required for connection to Ethernet port.

Steering, Standby and Emergency Compass Safe Distance 1.0 Degree deflection: 1100 mm

Standard Compass Safe Distance 0.3 Degree deflection: 1300 mm

## Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

### Product certificate

If specified in the Rules, ref. Pt.4 Ch.9 Sec.1, the control and monitoring system in which the above listed hardware is used shall be delivered with a product certificate. For each such delivery the certification test is to be performed at the manufacturer of the application system before the system is shipped to the yard. The test shall be done according to an approved test program. After certification the clause for software control will be put into force.

### Software control

All changes in software are to be recorded as long as the system is in use on board. Documentation of major changes is to be forwarded to DNV for evaluation and approval before implemented on board. Certification of modified functionality may be required for the particular vessel.

## Type Approval documentation

Report TL24010 Issue 1, HP Z4 G5 Workstation Unit A, dated 2024-04-16

Report TL24009 Issue 1, HP Z4 G5 Workstation Unit B, dated 2024-04-16

QuickSpecs HP Z4 G5 Workstation, c08482306 — DA 17147 – Worldwide — Version 22, dated 2024-04-01

Mariner Type Approval Test Requirements – Issue 17, dated 2023-06

Mariner Systems (UK) Ltd, HP Z4 G5 Workstation – Component Options, doc. HP Z4 G5 Workstation Components Apr 24 v1, dated 2024-04-17

Filter type RF 1010-MST-A. Dwg. No: DS 106-MST, Issue No.1.1, dated 2024-04-04

MS3120 Assembly Drawing. Dwg. No: MS3120\_A, dated 2024-03-14

MS3110 Assembly Drawing. Dwg. No: MS3110\_A, dated 2024-03-14

## Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021.

Shock test (15g, 11ms, repeated 20 times for each axis) according to EN 60068-2-27:2009.

Applicable tests for protected equipment according to IEC 60945, 4<sup>th</sup> edition (2002), except section 8.12 'Corrosion'.

### **Marking of product**

Mariner Kit Number + HP product label, as listed under Application/Limitation.

### **Periodical assessment**

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE